Resinify GuardPro

Safety Data Sheet (SDS) — per OSHA Hazard Communication Standard, 29 CFR 1910.1200

Document ID: RES-SDS-DENT-GRDPRO-Rev.A **Format:** GHS / OSHA HazCom 16-Section

Section 1: Identification

Product Name: Resinify GuardPro
Identified Uses: Resin for 3D printing of custom-fitted night guards and retainers for dental applications.

Supplier: Resinify Technology LLC, 22350 W. Warren Ave., Detroit, MI 48239 · (810) 888-7373

Emergency Contacts: CHEMTREC (Transportation): (800) 424-9300 (24/7) · Rocky Mountain Poison Center (Medical): (866) 767-5089 (24/7)

Section 2: Hazards Identification

GHS Classification

- Ethoxylated Trimethylolpropane Triacrylate: Skin Corrosion/Irritation Cat. 2; Eye Irritation Cat. 2A
- Urethane Dimethacrylate: Skin Corrosion/Irritation Cat. 2; Eye Irritation Cat. 2A
- Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide: Reproductive Toxicity Cat. 2 (H361)



Signal Word: Warning

Hazard Statements

- H315: Causes skin irritation
- H319: Causes serious eye irritation
- H317: May cause an allergic skin reaction
- H361: Suspected of damaging fertility or the unborn child

Precautionary Statements

- P201/P202: Obtain special instructions before use; do not handle until safety precautions are understood.
- P264/P280: Wash skin thoroughly after handling; wear protective gloves/clothing/eye/face protection.
- P302+P352 / P305+P351+P338: skin and eye response measures as above.
- P308+P313 / P362+P364 / P501: medical attention, decontamination, and disposal as above.

Section 3: Composition / Information on Ingredients

Ingredient	CAS No.	% by Weight
Urethane Dimethacrylate	Trade Secret	75%–85%

Ethoxylated Trimethylolpropane Triacrylate	Trade Secret	25%–15%
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	75980-60-8	<1%

Section 4: First-Aid Measures

- **Inhalation:** Remove from exposure to fresh air, restore breathing using oxygen if needed. Keep warm and quiet. Immediately notify a physician.
- **Skin Contact:** Wash affected area with soap and large amounts of water. Remove contaminated clothing. Consult a physician if irritation persists.
- **Eye Contact:** Immediately flush eyes with water for 15 minutes, holding eyelids open for complete irrigation. Remove contact lenses if worn. Take to a physician immediately.
- **Ingestion:** Do NOT induce vomiting. Have victim drink 8–10 ounces of water to dilute material in the stomach. Never give anything by mouth to an unconscious person. Consult a physician or poison control center.

Section 5: Fire-Fighting Measures

- Flash Point: 67°C (153°F) TCC · Auto-Ignition Temp: 400°C (752°F)
- Suitable Extinguishing Media: Foam, CO_2, Dry Chemical, Water-fog. Unsuitable: do not use waterjet.
- Dangerous fire hazard when exposed to heat or flame; heat can cause polymerization; closed containers may explode when exposed to extreme heat.
- Firefighters: wear self-contained breathing apparatus and turnout gear; isolate from all sources of ignition.
- Product freezes at 15°C/59°F; improper thawing can result in violent polymerization.

Section 6: Accidental Release Measures

- This material is corrosive; eliminate ignition sources in the vicinity of the spill. Evacuate nonessential personnel.
- Environmental precautions: keep out of water sources and sewers; do not flush into surface water or sanitary sewer.
- Containment/cleanup: use explosion-proof equipment; use non-flammable absorbent (clay or silica) for smaller spills; use foam to minimize vapors on larger spills.

Section 7: Handling and Storage

- This material is corrosive. Avoid prolonged or repeated contact with skin, eyes, and clothing. Use with adequate ventilation.
- Use non-sparking tools to open or close containers. Do not take internally.
- Store in original container, tightly closed, away from sources of heat and ignition. Protect from freezing. Store in a cool, dry, well-ventilated area away from sunlight.
- Maintain contact with atmosphere of 5–21% oxygen; storage stability of one year expected under proper conditions.

Section 8: Exposure Controls / Personal Protection

- Engineering Controls: ensure adequate ventilation, especially in confined areas. Provide eyewash stations and safety showers.
- Eye Protection: safety goggles or face shield.
- Skin Protection: suitable protective clothing and gloves (e.g., neoprene, nitrile).
- Respiratory Protection: NIOSH/MSHA-approved respiratory protection if exposure limits are exceeded or irritation is experienced.

Section 9: Physical and Chemical Properties

- Physical State: Liquid · Color: Clear · Odor: Mild · Flash Point: 67°C (153°F) TCC
- Solubility: Insoluble in water · Auto-Ignition Temp.: 400°C (752°F)

Section 10: Stability and Reactivity

- Reactivity: not reactive under normal conditions. Stability: stable under recommended storage conditions.
- Hazardous Reactions: hazardous polymerization may occur. Conditions to Avoid: heat, flames, sparks, other ignition sources.
- Incompatible Materials: strong oxidizing agents, acids, bases, and amines.
- Hazardous Decomposition Products: carbon oxides, nitrogen oxides, and other potentially toxic fumes.

Section 11: Toxicological Information

- Acute Toxicity: not determined for the mixture.
- Skin Corrosion/Irritation: causes skin irritation. Serious Eye Damage/Irritation: causes serious eye irritation.
- Respiratory or Skin Sensitization: may cause an allergic skin reaction.
- Reproductive Toxicity: suspected of damaging fertility or the unborn child.

Section 12: Ecological Information

- Toxicity, Persistence/Degradability, Bioaccumulative Potential, Mobility in Soil: no information available.
- Other Adverse Effects: no known significant effects or critical hazards.

Section 13: Disposal Considerations

- Dispose of in accordance with local, state, and federal regulations. Do not discharge into drains or the environment.
- Contaminated packaging: dispose of as unused product; do not reuse empty containers.

Section 14: Transport Information

- US DOT: UN 3082, Environmentally hazardous substance, liquid, n.o.s., Class 9, Packing Group III, Marine Pollutant: Yes.

- IMDG: UN 3082, same proper shipping name, Class 9, Packing Group III, Marine Pollutant: Yes, Flash Point >201°F (94°C).

Section 15: Regulatory Information

- TSCA: components are on the TSCA Inventory. Canadian DSL: components listed on DSL or NDSL.
- SARA Title III Section 311/312 Hazard Categories: Acute Health Hazard, Reactivity Hazard.
- SARA Title III Section 313: no components exceed De Minimis reporting thresholds.

Section 16: Other Information

Revision Date: 09.04.2024 · **Version:** 1 (rebrand Rev. A)

The information provided in this Safety Data Sheet is based on data considered accurate as of the date of preparation. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and safety information contained herein. Resinify Technology LLC assumes no responsibility for injury or damage resulting from inappropriate use of this product.

End of Safety Data Sheet